

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Cancelled)
2. (Previously Cancelled)
3. (Cancelled)
4. (Previously Cancelled)
5. (Cancelled)
6. (Previously Cancelled)
7. (Cancelled)
8. (Currently Amended) A worm drive clamp comprising:

a worm drive member having a body with at least one spiral thread on an outer surface thereof, a head disposed above an upper end of said body, and a pawled portion disposed below a lower end of said body; and

a flexible strap having a housing adapted to receive said drive member disposed toward a first end thereof, said strap being provided with a plurality of grooves on an inner surface thereof and with one or more indentations disposed between said grooves and [said] a second end thereof to temporarily hold said strap in engagement with said thread prior to rotation of said head,

wherein said housing has a ratcheted recess in a bottom wall thereof adapted to engage said pawled portion when said drive member is situated in said housing, and a slot in said bottom wall adapted to receive said second end of said strap; and

as said second end of said strap is inserted upward through said slot when said drive member is situated in said housing, said grooves engage said thread, such that as said worm drive member is rotated clockwise, said strap is drawn further upward through said slot, while said pawled portion is engaged by said ratcheted recess to prevent counterclockwise rotation.